#110-R-221760S

ALABAMA STATE LANDS TRAILER SPECIFICATIONS

DECK LENGTH:

30' LOW PROFILE W/ 31" DECK HEIGHT UNLOADED

DOVETAIL:

4' COVERED WITH 11/2" APITIONG LUMBER

WIDTH:

102" OVER THE WHEELS DESIGN

TONGUE:

8' LONG GOOSE NECK STYLE 70" GROUND TO BOTTO!

OF BEAM CLEARANCE/87" SWING CLEARANCE

MAINFRAME:

10" @ 19# PF WF I-BEAM WITH BRIDGE WORK

UNDER BOTTOM FOR EXTRA STRENGTH

SIDE RAIL:

6" CHANNEL WITH (11) D-RINGS PER SIDE START

24" FROM FRONT, 36" ON CENTERS. (7) 4" RATCHET

WINCH PER SIDE /START 36" FROM FRONT/ 48" ON CENTER OFF SET FROM D-RINGS WITH POCKETS ON OPPOSITE SIDE TO HOOK STRAP. 11/2 APITONG LUMBER FULL FLOOR ATTACHED

FLOORING:

WITH 5/16" TORX SCREWS METAL OVER TIRE AREA

25/16" GOOSENECK TYPE ADJUSTABLE

COUPLER:

FOR HEIGHT OF TRUCK

JACK:

AXLES:

(2) TWO SPEED WITH DROP LEG (25,000# CAPACITY)

(2) 12K DEXTER LOW PROFILE WITH OIL

BATH BEARING MULTI LEAF SUSPENSION

DEXTER BRAND (12,000# CAPACITY EACH)

BRAKE:

121/4" x 5" ELECTRICAL ALL WHEELS WITH BREAKAWAY KIT AND CHARGER FOR BATTERY

TIRES:

WHEELS: RAMPS:

(9) 9.00/14.5 LOAD RANGE F FOR LOW PROFILE (9) 8 LUG 14.5 BUDD TYPE

4" CHANNEL 18" WIDE 5' LONG WITH SUPPORT LEG

LIGHTS & WIRE:

AND SPRING ASSIST LIFT

FRAME MOUNTED/RUBBER CUSHIONED SEALED WIRING HARNESS/WITH SEALED

LED BULBS/NO BUTT OR SNAP CONNECTORS

INCLUDES:

TOOL TRAY & BOXES/ONE TRAY IN NECK ONE TOOL BOX ON RIGHT SIDE UNDER

BODY 14" H x 16" D x 36" L/SLOPE BOX BETWEEN UP RIGHTS ON FRONT/12"H x 12" D x 33" LONG/STEP FRONT & CENTER

DRIVER SIDE.

PAINT:

(2) COATS GRAY OXIDE PRIMER

PRIMED:

(2) COATS BLACK ACRYLIC ENAMEL

STANDARD WEIGHTS:

GROSS:

EMPTY:

25,500 LBS

AXLE:

12,000 LBS 9,000 LBS

BUSE TOET